

Safety Data Sheet

Version number: 12.1
SDS# R7501

2023-03-24

SECTION 1: Identification

1.1 Product identifier

| | |
|-------------------------------|--|
| Trade name | R-7501, R-7511, R-7518, R-7540, R-7540V, K-7553 Ampoules |
| Other means of identification | Dissolved Oxygen CHEMetrics® & ULR CHEMetrics® Re-fills and Vacu-vials® Ampoules |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|--|---|
| Component of water analysis test kits: | K-7501, K-7511, K-7518, K-7540, K-7553, K-7599, K-7599V |
|--|---|

1.3 Details of the supplier of the safety data sheet

CHEMetrics, LLC.
4295 Catlett Road
Midland VA 22728
United States

Telephone: 1-540-788-9026
Telefax: 1-540-788-4856
e-mail: technical@chemetrics.com
Website: www.chemetrics.com

1.4 Emergency telephone number

| | |
|-------------------------------|--|
| Emergency information service | ChemTel Inc.: 1-800-255-3924, +01-813-248-0585 |
|-------------------------------|--|

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class | Category | Hazard class and category | Hazard statement |
|---------|--|----------|---------------------------|------------------|
| 3.10 | acute toxicity (oral) | 4 | Acute Tox. 4 | H302 |
| 3.1I | acute toxicity (inhal.) | 5 | Acute Tox. 5 | H333 |
| 3.2 | skin corrosion/irritation | 1 | Skin Corr. 1 | H314 |
| 3.3 | serious eye damage/eye irritation | 1 | Eye Dam. 1 | H318 |
| 3.8 | specific target organ toxicity - single exposure | 2 | STOT SE 2 | H371 |

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labeling

- Signal word danger

- Pictograms

GHS05, GHS07, GHS08



- Hazard statements

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H333 May be harmful if inhaled.
 H371 May cause damage to organs.

- Precautionary statements

P260 Do not breathe dusts or mists.
 P264+P265 Wash hands thoroughly after handling. Do not touch eyes.
 P270 Do not eat, drink or smoke when using this product.
 P280 Wear eye protection/face protection.
 P301+P317 IF SWALLOWED: Get medical help.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+P361+P354 IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes.
 P304+P317 IF INHALED: Get medical help.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P354+P338 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.
 P316 Get emergency medical help immediately.
 P321 Specific treatment (see on this label).
 P363 Wash contaminated clothing before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container to industrial combustion plant.

2.3 Other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Classification acc. to GHS | Pictograms |
|---------------------|---------------------|-------------|---|------------|
| deionized water | CAS No 7732-18-5 | ≥ 67 | | |
| diethylene glycol | CAS No 111-46-6 | 27 – 31 | Acute Tox. 4 / H302 Acute Tox. 4 / H332 | |
| methanol | CAS No 67-56-1 | 3 – 4 | Flam. Liq. 2 / H225 Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 | |
| THAM | CAS No 77-86-1 | 0.25 | | |
| potassium hydroxide | CAS No 1310-58-3 | 0.09 | Acute Tox. 4 / H302 Skin Corr. 1A / H314 Eye Dam. 1 / H318 | |
| proprietary_06 | | 0.06 | Skin Irrit. 2 / H315 Eye Irrit. 2A / H319 STOT SE 3 / H335 | |
| proprietary_01 | | 0.01 – 0.02 | Water-react. 1 / H260 Acute Tox. 3 / H301 Acute Tox. 5 / H313 Acute Tox. 4 / H332 Skin Corr. 1C / H314 Eye Dam. 1 / H318 Repr. 1B / H360F Aquatic Acute 3 / H402 Aquatic Chronic 3 / H412 CDust001 | |
| proprietary_05 | | 0.001 | Acute Tox. 4 / H302 Acute Tox. 5 / H313 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410 | |

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Wear impact- and splash-resistant eyewear. Break the ampoule tip only when it is completely immersed in sample. Breaking the tip in air may cause the glass ampoule to shatter.

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

- Handling of incompatible substances or mixtures

Do not mix with acids.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

7.3 Other information

For optimum analytical performance, store in the dark and at room temperature.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|--------------------------------------|-----------|------------|------------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|------------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
| US | potassium hydroxide | 1310-58-3 | REL | | | | | | 2 | | NIOSH REL |
| US | potassium hydroxide | 1310-58-3 | TLV® | | | | | | 2 | | ACGIH® 2023 |
| US | potassium hydroxide (caustic potash) | 1310-58-3 | PEL (CA) | | | | | | 2 | | Cal/ OSHA PEL |
| US | methanol | 67-56-1 | TLV® | 200 | | 250 | | | | H | ACGIH® 2023 |
| US | methyl alcohol | 67-56-1 | REL | 200 (10 h) | 260 (10 h) | 250 | 325 | | | | NIOSH REL |
| US | methyl alcohol | 67-56-1 | PEL | 200 | 260 | | | | | | 29 CFR 1910.1000 |
| US | methyl alcohol (methanol) | 67-56-1 | PEL (CA) | 200 | 260 | 250 | 325 | 1,000 | | | Cal/ OSHA PEL |

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

| Country | Name of agent | Parameter | Notation | Identifier | Value | Source |
|---------|---------------|-----------|----------|------------|---------|-------------|
| US | methanol | methanol | | BEI® | 15 mg/l | ACGIH® 2023 |

Relevant DNELs of components of the mixture

| Name of substance | CAS No | Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
|---------------------|-----------|----------|-------------------------|------------------------------------|-------------------|----------------------------|
| diethylene glycol | 111-46-6 | DNEL | 44 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| diethylene glycol | 111-46-6 | DNEL | 60 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| diethylene glycol | 111-46-6 | DNEL | 43 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| methanol | 67-56-1 | DNEL | 130 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| methanol | 67-56-1 | DNEL | 130 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| methanol | 67-56-1 | DNEL | 130 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| methanol | 67-56-1 | DNEL | 130 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| methanol | 67-56-1 | DNEL | 20 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| methanol | 67-56-1 | DNEL | 20 mg/kg bw/day | human, dermal | worker (industry) | acute - systemic effects |
| THAM | 77-86-1 | DNEL | 117.5 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| THAM | 77-86-1 | DNEL | 166.7 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| potassium hydroxide | 1310-58-3 | DNEL | 1 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| proprietary_05 | | DNEL | 1 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| proprietary_05 | | DNEL | 1 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| proprietary_05 | | DNEL | 137 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

| Relevant PNECs of components of the mixture | | | | | | |
|---|----------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| diethylene glycol | 111-46-6 | PNEC | 10 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| diethylene glycol | 111-46-6 | PNEC | 1 mg/l | aquatic organisms | marine water | short-term (single instance) |
| diethylene glycol | 111-46-6 | PNEC | 199.5 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| diethylene glycol | 111-46-6 | PNEC | 20.9 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| diethylene glycol | 111-46-6 | PNEC | 2.09 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| diethylene glycol | 111-46-6 | PNEC | 1.53 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| methanol | 67-56-1 | PNEC | 20.8 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| methanol | 67-56-1 | PNEC | 2.08 mg/l | aquatic organisms | marine water | short-term (single instance) |
| methanol | 67-56-1 | PNEC | 100 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| methanol | 67-56-1 | PNEC | 77 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| methanol | 67-56-1 | PNEC | 7.7 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| methanol | 67-56-1 | PNEC | 100 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| THAM | 77-86-1 | PNEC | 300 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| proprietary_01 | | PNEC | 1.75 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| proprietary_01 | | PNEC | 1.75 mg/l | aquatic organisms | marine water | short-term (single instance) |
| proprietary_01 | | PNEC | 54.77 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| proprietary_01 | | PNEC | 2.55 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| proprietary_01 | | PNEC | 0.255 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| proprietary_01 | | PNEC | 4.8 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| proprietary_05 | | PNEC | 7.8 µg/l | aquatic organisms | freshwater | short-term (single instance) |
| proprietary_05 | | PNEC | 5.2 µg/l | aquatic organisms | marine water | short-term (single instance) |
| proprietary_05 | | PNEC | 230 µg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |

| Relevant PNECs of components of the mixture | | | | | | |
|---|--------|----------|-----------------|-----------------------|---------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| proprietary_05 | | PNEC | 87 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| proprietary_05 | | PNEC | 676 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| proprietary_05 | | PNEC | 65 mg/kg | terrestrial organisms | soil | short-term (single instance) |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Product description CHEMets Refills: Sealed glass ampoules, 7 mm OD, for visual colorimetric water analysis. Each CHEMet™ ampoule contains approximately 0.2 - 0.5 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

ULR CHEMets Refills: Sealed glass ampoules, 250 mm length, for visual colorimetric water analysis. Each ULR CHEMet™ ampoule contains approximately 1 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill

Vacu-vials Ampoules: Sealed glass ampoules, 13 mm OD, for instrumental colorimetric water analysis. Each Vacu-vial™ ampoule contains approximately 0.8 - 2 mL of liquid reagent sealed under vacuum. Test kits contain 30 ampoules.

Appearance

| | |
|----------------|------------------------------|
| Physical state | liquid |
| Color | Colorless to greenish yellow |
| Particle | not relevant (liquid) |
| Odor | odorless |

Other safety parameters

| | |
|---|-----------------------------------|
| pH (value) | 11.5 (base) |
| Melting point/freezing point | -5 °C |
| Initial boiling point and boiling range | 150 °C at 1,013 hPa |
| Flash point | not determined |
| Evaporation rate | Not determined |
| Flammability (solid, gas) | not relevant, (fluid) |
| Vapor pressure | 169.3 hPa at 25 °C |
| Density | not determined |
| Vapor density | this information is not available |
| Relative density | 1.03 (water = 1) |

Solubility(ies)

| | |
|--------------------|----------------------------|
| - Water solubility | miscible in any proportion |
|--------------------|----------------------------|

Partition coefficient

| | |
|-----------------------------|--|
| - n-octanol/water (log KOW) | this information is not available |
| Auto-ignition temperature | 372 °C (auto-ignition temperature (liquids and gases)) |
| Viscosity | not determined |
| Explosive properties | none |
| Oxidizing properties | none |

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4: May be harmful if inhaled.

- Acute toxicity estimate (ATE)

Oral 1,087 mg/kg

| Acute toxicity estimate (ATE) of components of the mixture | | | |
|--|----------|-----------------------|--------------|
| Name of substance | CAS No | Exposure route | ATE |
| diethylene glycol | 111-46-6 | oral | 500 mg/kg |
| diethylene glycol | 111-46-6 | inhalation: vapor | 11 mg/l/4h |
| diethylene glycol | 111-46-6 | inhalation: dust/mist | >4.6 mg/l/4h |
| methanol | 67-56-1 | oral | 100 mg/kg |
| methanol | 67-56-1 | dermal | 300 mg/kg |

| Acute toxicity estimate (ATE) of components of the mixture | | | |
|--|-----------|-----------------------|----------------------------|
| Name of substance | CAS No | Exposure route | ATE |
| methanol | 67-56-1 | inhalation: vapor | 3 mg _i /4h |
| potassium hydroxide | 1310-58-3 | oral | 333 mg/kg |
| proprietary_01 | | oral | 56.57 mg/kg |
| proprietary_01 | | inhalation: dust/mist | >1.295 mg _i /4h |
| proprietary_05 | | oral | 482 mg/kg |

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause damage to organs.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

please consider the relevant national or regional provisions

SECTION 14: Transport information**14.1 UN number**

not subject to transport regulations

14.2 UN proper shipping name**14.3 Transport hazard class(es)**

none

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Other relevant information

Shipping container markings and labels, received from CHEMetrics, may vary from the above information. Products that are regulated for transport will be packaged by CHEMetrics as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations. CHEMetrics may also elect to ship certain products as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III. In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations**Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

| Toxics Release Inventory: Specific Toxic Chemical Listings | | | |
|--|---------|---------|----------------|
| Name of substance | CAS No | Remarks | Effective date |
| methanol | 67-56-1 | | 1986-12-31 |

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

| Name of substance | Remarks | Statutory code | Final RQ pounds (Kg) |
|---------------------|---------|----------------|----------------------|
| potassium hydroxide | | 1 | 1000 (454) |
| methanol | | 3 4 | 5000 (2270) |

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

3 "3" indicates that the source is section 112 of the Clean Air Act

4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

| Proposition 65 List of chemicals | | | |
|----------------------------------|---------|---------|----------------------|
| Name acc. to inventory | CAS No | Remarks | Type of the toxicity |
| methanol | 67-56-1 | | developmental |

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

| Category | Rating | Description |
|---------------------|--------|--|
| Chronic | / | none |
| Health | 3 | major injury likely unless prompt action is taken and medical treatment is given |
| Flammability | 1 | material that must be preheated before ignition can occur |
| Physical hazard | 0 | material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive |
| Personal protection | - | |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

| Category | Degree of hazard | Description |
|----------------|------------------|--|
| Flammability | 1 | material that must be preheated before ignition can occur |
| Health | 3 | material that, under emergency conditions, can cause serious or permanent injury |
| Instability | 0 | material that is normally stable, even under fire conditions |
| Special hazard | | |

National inventories

| Country | Inventory | Status |
|---------|------------|--------------------------------|
| US | TSCA | not all ingredients are listed |
| AU | AIIC | not all ingredients are listed |
| CA | DSL | not all ingredients are listed |
| CN | IECSC | not all ingredients are listed |
| EU | ECSI | not all ingredients are listed |
| EU | REACH Reg. | not all ingredients are listed |
| JP | CSCL-ENCS | not all ingredients are listed |
| KR | KECI | not all ingredients are listed |
| MX | INSQ | not all ingredients are listed |
| NZ | NZIoC | not all ingredients are listed |
| PH | PICCS | not all ingredients are listed |
| TR | CICR | not all ingredients are listed |
| TW | TCSI | not all ingredients are listed |

Legend

| | |
|-----------|---|
| AIIC | Australian Inventory of Industrial Chemicals |
| CICR | Chemical Inventory and Control Regulation |
| CSCL-ENCS | List of Existing and New Chemical Substances (CSCL-ENCS) |
| DSL | Domestic Substances List (DSL) |
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| KECI | Korea Existing Chemicals Inventory |

Legend

| | |
|------------|---|
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision**Key literature references and sources for data**

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|-------|---|
| H225 | Highly flammable liquid and vapor. |
| H260 | In contact with water releases flammable gases, which may ignite spontaneously. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H311 | Toxic in contact with skin. |
| H313 | May be harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H333 | May be harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H360F | May damage fertility. |
| H370 | Causes damage to organs. |
| H371 | May cause damage to organs. |
| H400 | Very toxic to aquatic life. |
| H402 | Harmful to aquatic life. |

| Code | Text |
|------|---|
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.